



TRIBOMAR[®]
Oil Management Solutions

VISCOSITY & FUEL QUALITY

TriboFlash

TriboFlash PMCC Flash Point Tester
(PMCC = Pensky Martens Closed Cup)

- Power supply: AC 230Volt
- Heating power: 600 Watt
- Measuring range: 20 - 280°C
- Dimensions: 35 cm x 28 cm x 25 cm
- Weight: 6.0 kg



TriboFlash - PMCC Flash Point Tester

The TriboFlash is an onsite easy to handle flash point tester and is working in line with the specifications by the ASTM D93 – 11, DIN EN 22719 and ISO 2719:2002.

In many applications it is of vital importance to control the flash point of mineral fuel oils and lubricants to assure safe operation of machineries and engines. Low flash point can lead to severe damages and is an HSE issue which needs to be controlled and handled at any time - at any place.

TriboFlash's working range is from 20 to 280°C covering all the relevant fluids which could be tested onboard a ship or onsite in most of the land based industry.

Order No.: 1132

TRIBOMAR GmbH
Biedenkamp 3e
21509 Glinde/Hamburg
GERMANY

© 2013 TRIBOMAR GmbH. Changes and errors excepted.

Tel.: +49.40.73 09 13 99-0
Fax: +49.40.73 09 13 99 33

Email: info@tribomar.com
www.tribomar.com